

HOT TUB START-UP LIST

-Remove shrink wrap on spa, **INSPECT THE HOT TUB FOR ANY DAMAGE, NOTE ON THE SHIPPING BILL AND HAVE THE DRIVER ACKNOWLEDGE WITH SIGNATURE.**

-Locate spa equipment access door by locating brass number tag at the bottom right corner on cabinet.

*The number on the brass tag is your serial number

-Remove access door with a square head bit

-Install the electrical wire through cabinet wall or under spa, drilling a hole for wire access feed. The electrical wire enters spa pack on the left side for wire connections

***DO NOT MAKE ANY CHANGES INSIDE THE SPA PACK!**

*Spa Pack is 220 volt ready

-With power off, fill spa with garden hose until the water level is at the third slit down from the top of skimmer (this is a rectangular piece mounted on the inside spa wall with several slits in it.).

-Unscrew the bleeder valve on the filter lid just under the drink lid cover.

-This will “Hiss” as air is passed out of the system, when it stops, tighten the screw.

-Turn power on to the spa at breaker box.

*Digital topside on spa will flash current water temperature.

-Push pump 1 (1st button on left). Spa will start off slow for a few seconds until the air is pushed out from water lines.

-Spa is now primed and temperature can be adjusted to desired level.

*If 3 dots are flashing on topside, turn power off to spa, wait a few minutes and turn power back on – following previous procedure.

-If problem persist – see Spa Pack manual

-Pump 1 operates on 2 speeds, high and low, at the touch of the function button on the topside.

-Pump 2 operates on 1 speed, high and off. Leave pump off when spa is not in use.

-Place spa cover on spa to insulate while spa reaches set temperature.